

**TCB**

**GRANT OF EQUIPMENT  
AUTHORIZATION**

**TCB**

**Certification  
Issued Under the Authority of the  
Federal Communications Commission  
By:**

**Bay Area Compliance Laboratory Corp.  
1274 Anvilwood Avenue  
Sunnyvale, CA 94089**

**Date of Grant: 04/04/2022  
Application Dated: 04/04/2022**

**Sancon Inc.  
36 South 18th Avenue, Suite A  
Brighton, CO 80601**

**Attention: xiuzhen Wu**

**NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

**FCC IDENTIFIER:** 2AFC8T2  
**Name of Grantee:** Sancon Inc.  
**Equipment Class:** Licensed Non-Broadcast Transmitter Held to Face  
**Notes:** GMRS Two-way Radio

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	95E	462.55 - 462.725	1.585	2.5 PM	11K0F3E
	95E	462.5625 - 462.7125	1.589	2.5 PM	11K0F3E
	95E	467.55 - 467.725	1.581	2.5 PM	11K0F3E
	95E	467.5625 - 467.7125	0.401	2.5 PM	11K0F3E

Output power listed is ERP. This device is authorized to operate in GMRS (Part 95E) radio service. There must be an informational insert inside the box (product package) or the Users Manual must include information that clearly informs the consumer (buyer/owner) when the radio is transmitting on GMRS frequencies, that operation on GMRS frequencies requires an FCC license and such operation is subject to additional rules specified in 47 C.F.R. Part 95. This transmitter has been tested for SAR compliance in Push-to-Talk and body-worn operating configurations. The separation distance between user and the device or its antenna shall be at least 2.5 cm. Hand held and body-worn SAR compliance is limited to the specific antennas, belt-clips, holsters and accessories tested for this device. Users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. The highest reported SAR levels for head and body-worn accessories exposure conditions are 1.44 W/kg and 1.57 W/kg, respectively when operating at 50% duty factor.